


KS+ (Slow Speed Monobloc Pump)

RANGE AND TECHNICAL SPECIFICATIONS

Head Range : Upto 22 meters
 Discharge Range : Upto 72.5 LPS
 Power Rating : 2.2 - 7.5 kW
 Voltage Range : 300 - 440 V



Slow Speed Monobloc Pump

Approximate performance of KS+, 4 Pole, Monobloc Pump set rated voltage, 50 Hz, Three Phase A.C. power supply:

Pump Model	Power Rating kW	Pipe Size (mm)	Full Load Current (in Amps)	Rated Voltage (volts)	TOTAL HEADS IN METRES												RPM
					DISCHARGE IN LITRES PER SECOND												
					5	6	8	10	12	14	16	18	20	22			
KS-316+	2.2	3	65	50	4.9	-	-	-	-	13.4	11.6	9.3	-	-	-	1400	
KS-513+	3.7	5	100	100	7.6	415	-	34	30.9	27	22	-	-	-	-	1420	
KS-516+	3.7	5	80	65	7.6	415	-	-	-	23.7	20.8	17.5	13.2	-	-	1420	
KS-810+	5.5	7.5	150	150	11.9	400	66	63.5	55	49.5	-	-	-	-	-	1420	
KS-817+	5.5	7.5	100	100	11.9	400	-	-	34.4	31.8	29	25.3	19.2	-	-	1420	
KS-823+	5.5	7.5	100	80	11.9	400	-	-	-	27.3	25	22.2	18.8	14.5	-	1430	
KS-1012+	7.5	10	150	150	16	400	-	72.5	67	59.5	49.5	30	-	-	-	1430	
KS-1022+	7.5	10	100	100	16	400	-	-	-	-	36	33	29	24.2	17.5	1430	

Extended shaft version is also available on request for above pumpsets. These pumps can be supplied with stuffing box arrangement for gland packed or with mechanical seal. All pumpsets except KS-810+ and KS-1012+ are ISI marked.

KDT+ (Two Stage High Speed) / KDS+

RANGE AND TECHNICAL SPECIFICATIONS

Head Range : Upto 110 meters
 Discharge Range : Upto 30.4 LPS
 Power Rating : 3.7 - 15 kW (5 - 20 HP)
 Voltage Range : 300 - 440 V (Three Phase)



Pump Model	Power Rating (mm)	Pipe Size (mm)	Del.	Kw	TOTAL HEAD IN METERS												
					5	6	8	10	12	14	16	18	20	22			
KDT-544+	3.7	5	65	50	6.8	6.2	5.6	4.8	3.5	-	-	-	-	-	-	-	400
KDS-550++	3.7	5	50	40	4.1	3.7	3.3	2.7	2	-	-	-	-	-	-	-	400
KDT-588+	3.7	5	50	40	4.3	4	3.7	3.4	3	3.4	3	3.4	3	2.5	2	1.2	400
KDS-844+	5.5	7.5	65	65	10.3	9.5	8.4	7.1	4.7	-	-	-	-	-	-	-	400
KDT-844+	5.5	7.5	80	65	11.8	10.9	10	9	7.5	-	-	-	-	-	-	-	400
KDS-822+	5.5	7.5	65	50	8.6	8.1	7.5	6.8	5.9	4.5	-	-	-	-	-	-	400
KDT-864+	5.5	7.5	65	50	7.3	7	6.5	6	5.5	5	4.2	2.7	-	-	-	-	400
KDS-1050++	7.5	10	65	65	12.5	12	11.4	10.7	9.6	8.1	6	7.8	-	-	-	-	415
KDT-1050+	7.5	10	80	65	13.8	13.2	12.4	11.5	10.5	9.2	7.8	7.8	-	-	-	-	415
KDS-1065++	7.5	10	65	50	-	-	-	-	-	-	-	-	-	-	-	-	415
KDT-1078+	7.5	10	65	50	8.2	8	7.8	7.5	7.1	6.7	6.2	5.6	4.9	4	2	-	415
KDS-1348+	9.3	12.5	65	50	18.2	17.3	15.8	14.3	11.9	6	-	-	-	-	-	-	415
KDS-1360	9.3	12.5	65	50	12.5	12.1	11.7	11.2	10.75	10	9.2	-	-	-	-	-	415
KDT-1372+	9.3	12.5	65	65	-	-	-	-	-	-	-	-	-	-	-	-	415
KDS-1388+	9.3	12.5	65	50	-	-	-	-	-	-	-	-	-	-	-	-	415
KDS-1555+	11	15	80	65	-	-	-	-	-	-	-	-	-	-	-	-	415
KDS-1570+	11	15	65	50	-	-	-	-	-	-	-	-	-	-	-	-	415
KDS-1575+	11	15	65	50	-	-	-	-	-	-	-	-	-	-	-	-	415
KDT-1580+	11	15	65	50	-	-	-	-	-	-	-	-	-	-	-	-	415
KDT-1598+	11	15	65	50	-	-	-	-	-	-	-	-	-	-	-	-	415
KDS-2050+	15	20	100	80	30.4	28.8	27	25	22.8	19.4	13	-	-	-	-	-	415
KDT-2070+	15	20	80	65	-	-	-	-	-	-	-	-	-	-	-	-	415
KDT-2095+	15	20	65	65	-	-	-	-	-	-	-	-	-	-	-	-	415
KDS-2560+	18	25	100	80	-	-	-	-	-	-	-	-	-	-	-	-	415
KDS-3068+	22	30	100	80	-	-	-	-	-	-	-	-	-	-	-	-	415

Note: KDT+ : All pumpsets except KDT - 568+ and KDS - 844+ are ISI marked. KDS+ : All pumps except KDS - 1575+ are ISI marked. Above pumpset can be supplied with stuffing box arrangement for gland or with mechanical seal against the requirement. Performance applicable to liquid of specific gravity 1 and viscosity as of water.